

## Technical Data Sheet



# Concept™ Roofer



Light, strong and comfortable helmet with Premium 'Twist 2 Fit' Ratchet headband ensuring a secure fit.

<p>Specification</p>	<p>Colours:</p> <p>Peak:</p> <p>Size:</p> <p>Options:</p> <p>Accessories:</p> <p>Weight:</p> <p>Corporate Badging:</p> <p>Unique Features:</p> <p>Helmet Accessories Clip:</p> <p>Packaging:</p> <p>Code:</p>	<p>White (W), Green (G), Blue (B), Light Blue (LB), Orange (O), Yellow (Y), Red (R), Black (K), Grey (E) High Visibility Yellow (HVY) and High Visibility Orange (HVO) Full (40mm) or Reduced (20mm) 52-64cm Ventilation (crown and rear), Full Peak or Reduced Peak Compatible with  range of face and hearing accessories, VentPlugs for closing off ventilation (S30VP), Chinstrap (S30E), Retractable Eye Shield (S579) 331g (Full Peak), 330g (Reduced Peak) Front: 85 x 50mm or 25 x 60mm, Sides: 80 x 35mm Back: 100 x 20mm or 30 x 25mm Premium 'Twist 2 Fit' Ratchet, Ventplugs, Internal card holder for identification or medical information (credit card size 54 x 85mm) Use  accessories clips (S565) supplied with Carriers and Ear Defenders 10 per colour, box size 47 x 30 x 50cm, box weight 4.2kg S09E*R (Full Peak, Unvented) S09E*RJ (Full Peak, Vented) S08E*R (Reduced Peak, Unvented) S08E*RJ (Reduced Peak, Vented) *Insert Colour code of helmet (ie. W for White)</p>
<p>Materials</p>	<p>Shell:</p> <p>Cradle:</p> <p>Headband:</p> <p>Sweatband:</p> <p>Ratchet:</p>	<p>ABS (Acrylonitrile-Butadiene-Styrene) 6 Point Terylene webbing LDPE (Low Density Polyethylene) Hydro-Flock with 4mm foam Acetal with HDPE straps, Black foam 3mm</p> 
<p>Standard &amp; Options</p>	<p>Options within EN 397</p> <p>Options in addition to EN 397</p>	<p>European Standard - EN 397:1995+A1 / EN 397:2012+A1:2012 EN 50365 - Electrically insulating helmets for use on low voltage installations (1000V a.c.) 440V a.c. (Electrical Resistance) LD (Lateral Deformation) MM (Molten Metal) -30°C (Low Temperature Performance) 1000V a.c. (Electrical Resistance) -40°C (Low Temperature Performance) Note: Electrical Resistance and Molten Metal applicable to unvented shells only</p>
<p>Storage/Lifetime</p>	<p><u>Storage:</u></p> <ul style="list-style-type: none"> <li>- Can be stored and transported in their original cartons at ambient temperature (0°C to + 30°C)</li> <li>- May be stored in the dark for up to <b>5 years</b></li> <li>- Do not store in direct/high heat or sunlight as this may distort the shell</li> </ul> <p><u>Lifetime:</u></p> <ul style="list-style-type: none"> <li>- The Centurion helmet has an in-use life of up to <b>5 years</b></li> <li>- Excessive wear and tear can considerably reduce the lifespan of the product</li> </ul>	
<p>Cleaning</p>	<ul style="list-style-type: none"> <li>- Clean using warm soapy water and soft cloth</li> <li>- <b>Do not</b> use solvents or abrasives</li> </ul>	